

土 質 状 況 図

報 告 用 紙

調 査 名 福岡市立玄界診療所新築工事地質調査委託

調査年月日 6 年 9 月 日

調 査 地 点 福岡市西区大字玄界島字寄木1219-14

標 高 KBN 008 6.10 年 月 日

ボーリング孔：No. 2 機種

孔内水位(自然、泥) -1.90 m 調査責任者 水崎 和男

採取試料・原位置試験		貫入試験										標準				記録・観察・観				層厚				深さ		標高		標尺			
方注 1 2	深さ m	試験番号	測定番号	74μm通過質量百分率(%)										10cmごとの打撃回数				打撃回数 貫入量 N値	深さ m	記事	色調	土質名	土質記号	層厚 m	深さ m	標高 m	標尺 m				
				0	10	20	30	40	50	60	10	20	30	40	50	60															
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60	0	10	20	30	40	50	60
				0	10	20	30	40	50	60	0	10	20	30	40	50															

備考 注1) 試料採取方法の記号 注2) 原位置試験方法の記号

T: シンクオールサンデラー F: フォイルサンデラー
P: 標準貫入試験用サンデラー O: オーガー
D: デニソン型サンデラー