

千里納骨堂改築工事地質調査地質柱状図 (No. 7)

調査地点 福岡市西区千里 237

調査深度 19.00 m

区標 高 11.041 m 地下水位 GL-3.90 m

調査年月日 自昭和 年 月 日至 月 日

標尺	標高	深度	層厚	柱状図	色調	土質名	観察	相対密度	相対稠度	標準貫入試験										試料							
										深度 m	N 値 回/cm	10cm毎の 打撃回数			N 値					採取方法	採取番号						
												10 cm	20 cm	30 cm	10	20	30	40	50								
m	m	m	m																								
1.		0.10	0.10		灰 濃褐色	コンクリート 盛土	0.10~0.70m間 盛土からなり、礫入り砂質 シルト~砂質シルト状を呈す。	硬	1.151.														◎	(1)			
2.		0.70	0.60				0.70~1.50m間 産錐堆積物からなる。		非硬 常	1.45	13	4	4	5											◎	(2)	
3.							0.70~13.40m間 マサ土からなり、礫径φ2 ~5mmの石英粒を多く混 入した礫入り砂質シルト からなる。		硬	2.45	17	5	5	7											◎	(3)	
4.										3.153.	12	4	4	4											◎	(4)	
5.										3.45																◎	(5)
6.										4.154.	11	3	4	4												◎	(6)
7.										4.45																◎	(7)
8.										5.158	8	2	3	3												◎	(8)
9.										5.45																◎	(9)
10.										6.156	16	4	6	6												◎	(10)
11.										8.45																◎	(11)
12.										7.157	16	4	5	7												◎	(12)
13.										7.45																◎	(13)
14.										8.158	5	2	2	1												◎	(14)
15.										8.45																◎	(15)
16.										9.159	9	2	3	4												◎	(16)
17.										9.45																◎	(17)
18.										10.1510	11	3	4	4												◎	(18)
19.										10.45																◎	(19)
20.						11.1511	20	5	7	8												◎	(20)				
21.						11.45																◎	(21)				
22.						12.1512	22	6	8	8												◎	(22)				
23.						12.45																◎	(23)				
24.						13.0013	50	50														◎	(24)				
25.						13.22																◎	(25)				
26.						14.1514	47	13	14	20												◎	(26)				
27.						14.45																◎	(27)				
28.						15.1515	53	16	18	19												◎	(28)				
29.						15.45																◎	(29)				
30.						16.1516	50	15	17	18												◎	(30)				
31.						16.45																◎	(31)				
32.						17.0017	50	20	50	20												◎	(32)				
33.						17.20																◎	(33)				
34.						18.0018	50	50														◎	(34)				
35.						18.15																◎	(35)				

(注) 1. 試料採取方法の記号 (記号の右の数字は試料番号)

- — 1 乱さない試料
- ◎ — 2 貫入試験機による試料
- — 3 コア試料

2. 試料採取深度と回収比

3. 20	3.20~3.70は試料採取深度(m)
45/50	
3. 70	45/50は回収比(50cm:貫入深さ45cm試料長さ)

3. 標準貫入試験の項で10cm毎の打撃回数とは、最初の10cm貫入に要した打撃回数、10cm~20cmの間で要した打撃回数、20cm~30cmの間で要した打撃回数をそれぞれ示したものである。