

ボーリング(土質柱状図)

報告用紙

調査名・調査地点 赤田地区小宮校地質調査委託

標 高 7.980

調査年月日 平成27年2月27日～28日

ボーリング孔: No 5

孔内水位 1.10

調査担当者 諏訪真二

標 尺	深 さ	厚 さ	現 場 観 察 記 録				深 さ	打撃 回数	標準貫入試験				N 値						試料採取 番号	深 さ	採取 方法
			土質記号	土質名	色調	記 事			10cmごとの 打撃回数	10cm	20cm	30cm	0	10	20	30	40	50	60		
1	2.68	0.30	0.70	表土	茶褐色	断崖流入 土壌	1.15	22	5	8	9										
2	2.28	0.70	0.40	粘土	暗褐色		1.95	9	4	2	3										
3	2.05	0.95	0.25	粘土	暗褐色		2.45	38	11	13	14										
4	1.88	1.10					3.15	47	9	20	18										
5	3.28	4.70	5.75	砂	暗褐色	砂 20% 程度の粘土を含む 含水比大 全般的に粗砂	4.45	30	10	10	10										
6	2.38	5.60	0.90	砂	暗褐色	砂 20% 程度の粘土を含む 含水比大 花崗岩風化 砂 2% 程度の粘土を含む	5.45	45	16	17	12										
7				真砂	褐色	若干粘土を含む	6.15	22	6	7	9										
8				砂			7.45	22	7	8	7										
9							8.15	50/26	16	18	16/6										
10							9.41	50/20	21	29											
11	-3.30	11.28	5.68				10.15	50/3	31	19/3											
12							11.28														
13																					
14																					
15																					
16																					
17																					
18																					
19																					
20																					
21																					
22																					
23																					
24																					
25																					
26																					
27																					
28																					
29																					
30																					

備考:

試料採取方法の記号

- シンクウォールサンプラー
- 貫入試験用サンプラー

- バンソウ型サンプラー
- ⊕ フィールサンプラー
- × その他

375